

connAV

Spec Sheet




Power Rating:	50w 90v-230v 50/60Hz
Connections:	PowerCON True1 (in and out) Rear PowerCON True1 Out Front 2 x HDMI Out 1x HDMI In 1x BNC SDI IN 1 x BNC SDI Out 4 x Ethercon Halo 1 x USB C 4 x XLR 3Pin (Audio In & Out)
Finish:	Powdercoat Black
Enclosure:	3mm Steel
Weight:	3Kg
Dimensions (HWD):	44, 482, 220mm
HDMI Input	HDMI 1.4 supports up to 4K@30fps
SDI Input	3G-SDI, up to 1080P60
Supported Input Resolutions	4K30, 1080P, 720P, 1080i, 720i, 1600x1200, 1440x900, 1366x768, 1280x1024, 1024x768, 800x600, 640x480
Encoding Format	H.264, H.265, MJPEG/JPEG Main and Baseline Profiles
Decoding Format	H264, H265, MJPEG
Encoding Resolution	Main: 4K, 1080P, 720P, 360P, Sub: 720P, 360P
Frame Rate	1-60 fps Adjustable
Maximum Bit Rate	40Mbps
Rate Control	CBR/VBR/AVBR/FIXQP/QPMAP
Network Transfer Protocol	RTSP, RTMP, HTTP, HLS, UDP, Unicast, Multicast, ONVIF, SRT, NDI
Network Interface	4 x Ethercon with built in 5 port switch
User Interface	WEB configuration, parameter hot update, firmware upgrade, network setting, password management, upload watermark logo/images
Finish:	Powdercoat Black
Enclosure:	3mm Steel
Weight:	3Kg

Trade Descriptions Act

Due to Apt-GB's policy of continuing improvement, we reserve the right to alter the specification without prior notice.

Every Apt-GB product is built to the highest manufacturing standards and rigorously tested to ensure that it meets the performance criteria specified in the design.



Tel: +44 (0) 1579 212210
Email: info@apt-gb.com
Website: www.apt-gb.com

